

Servoreeler® Systems Product List

Basic Suspended Microphone Servoreelers

Model	Description	Cable Capacity
SRL-4	Audix	4' (1.2m) (Audix cable)
SRL-8	Servoreeler	8' (2.45m)
SRL-8P	Polycom HDX	8' (2.45m)
SRL-8CL1	ClearOne Array	8' (2.45m)
SRL-20	Servoreeler	23' (8m)
SRL-20P	Polycom HDX	23' (8m)
SRL-20CL1	ClearOne Array	23' (8m)
SRL-40	Servoreeler	43' (14m)
SRL-90	Servoreeler	100' (29m)
SRL-90A	.25" (6mm) dia.cable	+35' (10.5m)
SRL-90MC	Special shielded-multi-pair or multi-quad 6mm cable	

NOTE: Customer specified multi-pin connectors priced according to cost. Cable capacities are nominal. Cable color: Black or White.

Servoreeler Options

No Suffix	Standard XLR female cable and male chassis connectors
SRL-S	Stereo configuration: Four conductor shielded cable and five pin XLR connectors; pricing below
(S) Pricing	SRL-8 & 20 = 1 x price; SRL-40 = 2 x price; SRL-90 = 3 x price
SRL-H	Horizontal Servoreeler configuration
SRL-L	Labor to install Lemo or other 3 - 5 pin connector

Modular Controller Main Frames **NOTE: Include one Option-A or B for each Controller ordered if not part of an SRS System**

SRC-6	(1 – 6) Servoreeler Controller/Power supply
SRC-12	(1 – 12) Servoreeler Controller/Power supply
Option-A*	Plug-in control card for above: for each Servoreeler
Option-B**	Option-A control card & Pushbutton Station
NOTE: Option-A control cards and Pushbutton Stations are installed into the SRC main frame at the factory	
WP1-2	Wall Plate - Double Servoreeler Controller - ★
	★ <i>Consists of single Option-B; Selectable - one, two or both Servoreelers. Requires a (PS-24) 24vdc supply</i>
PS-24	24Vdc regulated supply for WP1-2 Controller

Accessories and Attachments

BRK-1	Universal microphone bracket for use with trapeze bar
BZ-1	Switched ceiling dress bezel 2.150" L
BZ-2	Switched ceiling dress bezel (Long) 3.200" L
BZ-2L	Switched ceiling bezel (Extra Long for Audix) 4.500" L
BZ-3	Polycom/ClearOne switched ceiling bezel 4.500" L
BZ-H	Horizontal pulley bezel adapter
BZ-3H	BZ-H with adapter to fit BZ-3
CP-1	Non-marring 2mm cable clamp
ENC	Encoder output
HCB-8	Ceiling Access Door
HR-[]	Hand remote (basic housing) (1-10 station housing)
MPS-2	Monofilament positioning Servoreeler
SCB-24	Ceiling Bridge 24" (also available for horizontal operation SCB-24H)
SRS-DT	Decca Tree (2m x 1.5m "T") (Requires 3 - BRK-1)
STA - #	Specify [#] of up-down stations. Cost per station:
TL - #	Trapeze: Cost for each additional foot (300mm)
TRAP-[1']	Trapeze bar: ¾" dia. x 1ft. long with 2 CP-1 clamps

Microphone Options

RM-1	Shure MX-202 Specify Cardioid or Super-cardioid; Black or White
RM-1 MOD	Modification to shorten MX-202
RM-2	Ball microphone: Omni - ¾" diameter stainless steel
RM-L	Legislative style, hand-held, clip-on microphone
RM-X	Labor to install user defined or supplied microphone

Pull-Activated Servoreelers as Employed in Legislative Installations

SRP-8	Servoreeler	8' (2.45m)
-------	-------------	------------

***Control Option-A** Permits control by an external computer or remote control station via a multi-pin connector output.

****Control Option-B** In increments of two stations; provides Option-A functions adding individual up-down pushbutton control stations for each Servoreeler located on the controller front panel. Servoreeler functions are indicated by LED mode indicators on each pushbutton.

NOTICE: Please confirm our latest pricing prior to quoting a project; individual prices are subject to change.

